

E5785-92c Specification



Product Model			E5785-92c
Key Specification	Band	LTE Bands	LTE FDD: B1/3/7/8/20 LTE TDD: B38/40/41 (2555~2655MHz) /42(3500~3600MHz) /43 LTE CA: B1+B3, B1+B8, B1+B20, B3+B7, B3+B8, B3+B20, B3+B42, B3+B43, B7+B20 UL CA : Intra-Band continuous : B42+B42,B43+B43 DL CA: Intra-Band continuous : B3+B3, B7+B7, B38+B38, B40+B40, B41+B41, B42+B42, B43+B43 Intra-Band non-continuous : B3+B3, B41+B41 See Appendix for supported LTE channel bandwidths
		UMTS Bands	3G:B1/8
		GSM Bands	NA
	Product Form		Built-in antenna
			Size:108*62*17.3mm, Weight : ~125g
	Basic Characteristics		Speed : FDD:300/50Mbps @40M BW TDD:224/20Mbps @40M BW
			Battery Capacity : 3000mAh, Working time:12h, Standby time:700h
			WiFi : 802.11b/g/n/ac 2*2 2.4G&5G , Support 16 user
			SIM Card : micro SIM card slot
			Display : 1.45inch LCD
			External antenna : NA
			Support EMUI10.0 Router , QR code easy connection
			Charge : 17cm USB charging line , charger (optional)